Detector Switch MSS-25



Sliding contact type.

For micro current.

Normally closed type.

Applications

∽Multi-functional Fax

- ◆CD, DVD-ROM
- ◆Car audio

Typical Specifications



Actual size

Zoom

No	Products No	Poles	Positions	Operating force
1	MSS-25	1	1	0.79N max

Typical Specifications

Items	Specifications
Ratings	10mA 16V DC (Resistive load)
Contact resistance	1 ohm max
Insulation resistance	100 megohm min.250V DC
Withstanding voltage	250V AC for 1min
Operating life	25,000 cycles

MSS-25

Dimensions



Notes

- The appearance and specifications of the product may be modified without prior notice to improve its performance. 1.
- $\mathbf{2}$. This catalog shows only outline specifications. When using the product, please obtain formal specifications supply.
- 3. Please see appendix [Cautions in Using Switches].
- For high safety applications, please confirm with protection and redundant circuit. 4.
- 5.This detector switch is not a washable type.
- In manual soldering, consideration should be given to apply the soldering iron to the tip of the terminal so that 6. unusual pressure is not applied to the terminal.
- 7. Please do not apply pressure for 1 minute after soldering.
- 8. Since soldering quality may deteriorate due to sulfuration and oxidation of terminals, please use as soon as possible within maximum 6 months after delivery and use within a after opening the package condition and the one within 1 week after you unpack it again.
- 9. Please confirm the performance on actual operation by simulation with actual environment environments for high reliability.